



AM-1900DSP

Technical datasheet

Channels	1 x 1500 W RMS for LF and MF + 1 x 500 W RMS for HF.
Protection	Surge protection up to 265 V AC, output protection against overload, clip, limiter.
Input type	Balanced.
Input impedance	20000 ohms.
Input sensitivity	6.2 V (+18 dBu).
DSP	24 Bit / 96 KHz. 6 factory presets with on-screen selection button.
Pro DG net	1 RS485 input + 1 output link RS485 for network control of the entire system.
Connectors	1 x XLR female (input signal), 1x XLR male (output link). 1 x Speakon output for passive unit AVIATOR LA 210 P (exclusively in the model AVIATOR LA 210 A). PowerCON NAC3FCB (current supply).
Controls	On / off switch and master volume. Preset selector cursor.
Power supply	AC 90~265V - 50 / 60HZ.
Construction	Sheet steel enclosure with aluminum front cover. Special oven-dried electrostatic paint finish in black colour.
Dimensions (height x width x depth)	95 x 330 x 140 mm (3,74 x 12,99 x 5,51 in).
Weight	2,5 Kg (5,51 lbs) net / 3 Kg (6,61 lbs) with packaging.

The information included in this document may be changed without prior notice. To stay up to date with the latest version of this document, we recommend that you periodically consult Pro DG Systems website: www.prodgsystems.com