



AM-IRIS-SUB

Technical datasheet

Channels	1 x 1000 W RMS for LF + 1 x 600 W RMS for MF and HF.
Protection	Overvoltage protection up to 135/264 V AC, output overload protection, clip, limiter.
Input type	Balanced.
Input impedance	20000 ohms.
Input sensitivity	2 V (+8 dBu).
DSP	24 Bit / 96 KHz. 4 factory presets with selection button.
Connectors	2 XLR/Jack combo inputs, with microphone and line selector on channel 2 + XLR link. Bluetooth connection and TWS function. PowerCON (current supply).
Controls	On/Off switch, independent top and subwoofer volume controls, Line/Mic switch, Bluetooth on/off switch, TWS switch, DSP preset selector.
Power supply	100~240V 50/60Hz with voltage selector.
Construction	Sheet steel enclosure with aluminum front cover. Special oven-dried electrostatic paint finish in black colour.
Dimensions (height x width x depth)	95 x 417 x 154 mm (3,74 x 16,42 x 6,06 in).
Weight	2 Kg (4,41 lbs) net / 2,3 Kg (5,07 lbs) with packaging.

The information included in this document may be changed without prior notice. To stay up to date with the latest version of this document, we recommend that you periodically consult Pro DG Systems website: www.prodgsystems.com