



AVIATOR LA 210 P

Technical datasheet	
Power handling	700 W RMS / 1400 W program / 2800 W peak.
Maximum SPL Calculation	1m / 128 dB continuous / 131 dB program / 134 dB peak.
Nominal impedance	8 Ohm.
Frequency range	70 - 20000 Hz.
Dispersion angle	90° horizontal. Vertical dependent on distribution.
MF and LF components	Two Lavoce Italiana 10" speakers. Neodymium. 300 W RMS (per unit).
HF component	One Lavoce Italiana 1/4" compression driver. Neodymium. 100 W RMS.
Frequency cut-off for MF *	90 Hz Linkwitz-riley 24 filter - 1200 Hz Linkwitz-riley 24 filter.
Frequency cut-off for HF *	1200 Hz Linkwitz-riley 24 filter - 18 kHz Linkwitz-riley 24 filter.
Frequency cut-off for subwoofer *	Up to 90 Hz. Linkwitz-riley 24 filter.
Connectors	2 x Speakon NL4 MP.
Construction	Birch plywood using CNC machining. 2mm thick perforated steel front grille, with oven-dried black electrostatic powder paint finish. Includes acoustic foam.
Paint	Special polyurea finish resistant to impacts and inclement weather. Black color (standard).
Dimensions (height x width x depth)	291 x 865 x 474.5mm (11,46 x 34,06 x 18,68in).
Weight	30,5 Kg (67,24 lbs) net / 33,5 Kg (73,85 lbs) with packaging.

* Disrespect the suggested frequency cuts-off on the different ways may cause components breakage.

The information included in this document may be changed without prior notice. To stay up to date with the latest version of this document, we recommend that you periodically consult Pro DG Systems website: www.prodgsystems.com