



AVIATOR S 118 P

Technical datasheet	
Power handling	1500 W RMS / 3000 W program / 6000 W peak.
Maximum SPL Calculation	1m / 132 dB continuous / 135 dB program / 138 dB peak.
Nominal impedance	8 Ohm.
Frequency range	35 - 125 Hz.
Dispersion angle	Omnidirectional.
Components	One Lavoce Italiana 18" speaker. Ferrite. 1500 W RMS.
Recommended Frequency cut-off *	Up to 90 Hz. Linkwitz-riley 24 filter.
Connectors	2 x Speakon NL 4 MP.
Construction	Birch plywood using CNC machining. 2mm thick perforated steel front grille, with oven-dried black electrostatic powder paint finish. Includes acoustic foam. Includes stand socket to attach extendable bar.
Paint	Special polyurea finish resistant to impacts and inclement weather. Black color (standard).
Dimensions (height x width x depth)	698 x 520,7 x 723,9mm (27,48x20,50x28,50in).
Weight	50,5 Kg (111,33 lbs) net / 53,5 Kg (117,95 lbs) with packaging.

* Disrespect the suggested frequency cuts-off on the different ways may cause components breakage.

The information included in this document may be changed without prior notice. To stay up to date with the latest version of this document, we recommend that you periodically consult Pro DG Systems website: www.prodgsystems.com