

IBIZA LA 210 A

Technical datasheet	
Power handling	1500 W RMS / 3000 W program / 6000 W peak.
Maximum SPL Calculation	1m / 132 dB continuous / 135 dB program / 138 dB peak.
Nominal impedance	8 Ohm.
Frequency range	60 - 20000 Hz.
Dispersion angle	90º horizontal. Vertical dependent on distribution.
MF and LF components	Two Beyma 10" speakers. Neodymium. 700 W RMS (per unit).
HF component	One Beyma 1/4" compression driver. Neodymium. 100 W RMS.
Frequency cut-off for MF *	90 Hz Linkwitz-riley 24 filter - 1200 Hz Linkwitz-riley 24 filter.
Frequency cut-off for HF *	1200 Hz Linkwitz-riley 24 filter - 18 kHz Linkwitz-riley 24 filter.
Frequency cut-off for subwoofer *	Up to 90 Hz. Linkwitz-riley 24 filter.
Amplifier	State-of-the-art Class-D. 1 x 1500 W RMS for LF and MF+ 1 x 500 W RMS for HF. Surge protection up to 265 V AC, output protection against overload, clip, limiter.
	Input type: balanced. Input impedance: 20000 ohms. Input sensitivity: 6.2 V (+18 dBu).
DSP	24 Bit / 96 KHz. 6 factory presets with on- screen selection button.
Pro DG net	1 RS485 input + 1 output link RS485 for network control of the entire system.
Connectors	1 x XLR female (input signal), 1x XLR male (output link). PowerCON NAC3FCB (current supply).
Controls	On / off switch and master volume. Preset selector cursor.
Power supply	AC 90~265V - 50 / 60HZ.

Construction	Birch plywood using CNC machining. 2mm thick perforated steel front grille, with ovendried black electrostatic powder paint finish. Includes acoustic foam.
Paint	Special polyurea finish resistant to impacts and inclement weather. Black color (standard).
Dimensions (height x width x depth)	291 x 865 x 474.5mm (11,46 x 34,06 x 18,68in).
Weight	34,5 Kg (76,06 lbs) net / 37,5 Kg (82,67 lbs) with packaging.

The information included in this document may be changed without prior notice. To stay up to date with the latest version of this document, we recommend that you periodically consult Pro DG Systems website: www.prodgsystems.com

^{*} Disrespect the suggested frequency cuts-off on the different ways may cause components breakage.