



IBIZA S 218 A

Technical datasheet	
Power handling	3200 W RMS / 6400 W program / 12800 W peak.
Maximum SPL Calculation	1m / 136 dB continuous / 139 dB program / 142 dB peak.
Nominal impedance	4 Ohm.
Frequency range	30 - 125 Hz.
Dispersion angle	Omnidirectional.
Components	Two Beyma 18" speakers. Neodymium. 1600 W RMS (per unit).
Recommended Frequency cut-off *	Up to 90 Hz. Linkwitz-riley 24 filter.
Amplifier	<p>State-of-the-art Class-D. 2 x 2000 W RMS @ 8 Ohm.</p> <p>Surge protection up to 265 V AC, output protection against overload, clip, limiter.</p> <p>Input type: balanced.</p> <p>Input impedance: 20000 ohms.</p> <p>Input sensitivity: 4.9 V (+16 dBu).</p>
DSP	24 Bit / 96 KHz. 6 factory presets with on-screen selection button.
Pro DG net	1 RS485 input + 1 output link RS485 for network control of the entire system.
Connectors	<p>1 x XLR female (input signal), 1x XLR male (output link).</p> <p>PowerCON NAC3FCB (current supply).</p>
Controls	On / off switch and master volume. Preset selector cursor.
Power supply	AC 90~265V - 50 / 60HZ.
Construction	<p>Birch plywood using CNC machining. 2mm thick perforated steel front grille, with oven-dried black electrostatic powder paint finish. Includes acoustic foam.</p> <p>Incorporates stand socket for extendable bar fixation.</p>
Paint	Special polyurea finish resistant to impacts and inclement weather. Black color (standard).

Dimensions (height x width x depth)	525 x 1240 x 665mm (20,67 x 48,82 x 26,18in).
Weight	89,5 Kg (197,31 lbs) net / 94 Kg (207,24 lbs) with packaging.

* Disrespect the suggested frequency cuts-off on the different ways may cause components breakage.

The information included in this document may be changed without prior notice. To stay up to date with the latest version of this document, we recommend that you periodically consult Pro DG Systems website: www.prodgsystems.com